
 Caños de 5" a 8".

Ø Exterior		Espesor de pared		Peso
pulg.	mm	sch. n°	mm	kg/m
5	141.30	-	2.11	7.24
5	141.30	-	3.18	10.81
5	141.30	-	3.96	13.42
5	141.30	-	4.78	16.07
5	141.30	-	5.56	18.62
5	141.30	40-STD	6.55	21.76
5	141.30	-	7.14	23.61
5	141.30	-	7.92	26.05
5	141.30	-	8.74	28.55
5	141.30	80-XS	9.52	30.94
5	141.30	120	12.70	40.26
5	141.30	160	15.88	49.08
5	141.30	XXS	19.05	57.41
6	168.30	-	2.11	8.64
6	168.30	-	2.77	11.31
6	168.30	-	3.18	12.93
6	168.30	-	3.58	14.54
6	168.30	-	3.96	16.06
6	168.30	-	4.37	17.65
6	168.30	-	4.78	19.24
6	168.30	-	5.16	20.73
6	168.30	-	5.56	22.31
6	168.30	30	6.35	25.35
6	168.30	40-STD	7.11	28.26
6	168.30	-	7.92	31.34
6	168.30	-	8.74	34.38
6	168.30	-	9.52	37.28
6	168.30	80-XS	10.97	42.56
6	168.30	-	12.70	48.72
6	168.30	120	14.27	54.20
6	168.30	-	15.88	59.65
6	168.30	160	18.26	67.55
6	168.30	XXS	21.95	79.18
8	219.10	-	3.18	16.91
8	219.10	-	3.96	21.02
8	219.10	-	4.78	25.23

 Caños de 5" a 8".

Ø Exterior		Espesor de pared		Peso
pulg.	mm	sch. n°	mm	kg/m
8	219.10	-	5.16	27.20
8	219.10	-	5.56	29.28
8	219.10	20	6.35	33.31
8	219.10	30	7.04	36.79
8	219.10	-	7.92	41.26
8	219.10	40-STD	8.18	42.53
8	219.10	-	8.74	45.31
8	219.10	-	9.52	49.21
8	219.10	60	10.31	53.09
8	219.10	-	11.13	57.05
8	219.10	80-XS	12.70	64.63
8	219.10	-	14.27	72.09
8	219.10	100	15.09	75.89
8	219.10	-	15.88	79.54
8	219.10	120	18.26	90.43
8	219.10	140	20.62	100.93
8	219.10	XXS	22.22	107.87
8	219.10	160	23.01	111.25