



**Tabla de Cuplas de Reducción Serie 2000 y 3000 – Roscado y S.W.**

Tamaño pulq.	A Roscado mm	B Roscado mm	A S.W. mm	B S.W. mm	C Min. mm	D Max. mm	E Max. mm	F Max. mm
1/4 x 1/8	19.00	35.00	22.00	28.00	10.00	14.35	7.60	10.90
3/8 x 1/4	22.00	38.00	25.40	29.00	10.00	17.80	10.00	14.35
1/2 x 3/8	29.00	48.00	31.70	33.00	10.00	21.95	13.30	17.80
3/4 x 1/2	35.00	51.00	38.10	39.00	13.00	27.30	16.60	21.95
1 x 3/4	44.40	60.00	44.40	43.00	13.00	34.05	21.70	27.30
1 1/4 x 1	57.00	67.00	57.00	43.00	13.00	42.80	27.40	34.05
1 1/2 x 1 1/4	64.00	79.00	64.00	43.00	13.00	48.90	35.80	42.80
2 x 1 1/2	76.00	86.00	76.00	55.00	16.00	61.35	41.70	48.90
2 1/2 x 2	92.00	92.00	92.00	56.00	16.00	74.20	53.50	61.35
3 x 2 1/2	108.00	108.00	108.00	56.00	16.00	90.15	64.20	74.20
4 x 3	140.00	121.00	140.00	62.00	16.00	115.80	79.50	90.15

**Tabla de Cuplas de Reducción Serie 6000 – Roscado y S.W.**

Tamaño pulq.	A Roscado mm	B Roscado mm	A S.W. mm	B S.W. mm	C Min. mm	D Max. mm	E Max. mm	F Max. mm
1/4 x 1/8	22.00	35.00	24.00	28.00	10.00	14.35	4.8	10.9
3/8 x 1/4	25.00	38.00	29.00	29.00	10.00	17.80	7.10	14.35
1/2 x 3/8	32.00	48.00	35.00	33.00	10.00	21.95	9.90	17.80
3/4 x 1/2	38.10	51.00	41.20	39.00	13.00	27.30	12.50	21.95
1 x 3/4	44.40	60.00	50.80	43.00	13.00	34.05	16.30	27.30
1 1/4 x 1	57.00	67.00	57.00	43.00	13.00	42.80	21.50	34.05
1 1/2 x 1 1/4	64.00	79.00	67.00	43.00	13.00	48.90	30.20	42.8
2 x 1 1/2	76.00	86.00	83.00	55.00	16.00	61.35	34.70	48.90
2 1/2 x 2	92.00	92.00					53.50	
3 x 2 1/2	108.00	108.00					64.20	
4 x 3	140.00	121.00					79.50	