



 Tabla de Cuplas Serie 2000 y 3000 – Roscado y S.W.

Tamaño		A Roscado	B Roscado	A S.W.	B S.W.	C Min.	D Max.	E Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	16.00	32.00	17.00	28.00	10.00	10.90	7.60
1/4	6.40	19.00	35.00	22.00	28.00	10.00	14.35	10.00
3/8	9.50	22.00	38.00	25.40	29.00	10.00	17.80	13.30
1/2	12.70	29.00	48.00	31.70	33.00	10.00	21.95	16.60
3/4	19.00	35.00	51.00	38.10	39.00	13.00	27.30	21.70
1	25.40	44.40	60.00	44.40	43.00	13.00	34.05	27.40
1 1/4	31.80	57.00	67.00	57.00	43.00	13.00	42.80	35.80
1 1/2	38.00	64.00	79.00	64.00	43.00	13.00	48.90	41.70
2	51.00	76.00	86.00	76.00	55.00	16.00	61.35	53.50
2 1/2	63.50	92.00	92.00	92.00	56.00	16.00	74.20	64.20
3	76.00	108.00	108.00	108.00	56.00	16.00	90.15	79.50
4	102.00	140.00	121.00	140.00	62.00	19.00	115.80	103.80

 Tabla de Cuplas Serie 6000 – Roscado y S.W.

Tamaño		A Roscado	B Roscado	A S.W.	B S.W.	C Min.	D Max.	E Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	22.00	32.00	19.00	28.00	10.00	10.90	4.80
1/4	6.40	25.00	35.00	24.00	28.00	10.00	14.35	7.10
3/8	9.50	32.00	38.00	29.00	29.00	10.00	17.80	9.90
1/2	12.70	38.10	48.00	35.00	33.00	10.00	21.95	12.50
3/4	19.00	44.40	51.00	41.20	39.00	13.00	27.30	16.30
1	25.40	57.00	60.00	50.80	43.00	13.00	34.05	21.50
1 1/4	31.80	63.50	67.00	57.00	43.00	13.00	42.80	30.20
1 1/2	38.00	76.00	79.00	67.00	43.00	13.00	48.90	34.70
2	51.00	92.00	86.00	83.00	65.00	16.00	61.35	43.60
2 1/2	63.50	108.00	92.00			16.00	74.20	
3	76.00	127.00	108.00			16.00	90.15	
4	102.00	159.00	121.00			19.00	115.80	