



 Tabla de Medias Cuplas Serie 3000 – Roscado y S.W.

Tamaño		A Roscado	B Roscado	A S.W.	B S.W.	D Min.	F Max.	H Max.
pulg.	mm	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	16.00	16.00	17.00	27.00	10.00	10.90	7.60
1/4	6.40	19.00	17.50	22.00	27.00	10.00	14.35	10.00
3/8	9.50	22.00	19.00	25.40	29.00	10.00	17.80	13.30
1/2	12.70	29.00	24.00	31.70	34.00	10.00	21.95	16.60
3/4	19.00	35.00	25.50	38.10	38.00	13.00	27.30	21.70
1	25.40	44.40	30.00	44.40	44.00	13.00	34.05	27.40
1 1/4	31.80	57.00	33.50	57.00	45.00	13.00	42.80	35.80
1 1/2	38.00	64.00	39.50	64.00	47.00	13.00	48.90	41.70
2	51.00	76.00	43.00	83.00	59.00	16.00	61.35	53.50
2 1/2	63.50	92.00	46.00	92.00	61.00	16.00	74.20	64.20
3	76.00	108.00	54.00		63.00	16.00	90.15	79.50
4	102.00	140.00	60.50		69.00	19.00	115.80	103.80

 Tabla de Medias Cuplas Serie 6000 – Roscado y S.W.

Tamaño		A Roscado	B Roscado	A S.W.	B S.W. Max	C Min.	D Max.
pulg.	mm	mm	mm	mm	mm	mm	mm
1/8	3.20	22.00	16.00	19.00	27.00	10.00	10.90
1/4	6.40	25.00	17.50	24.50	27.00	10.00	14.35
3/8	9.50	32.00	19.00	29.00	29.00	10.00	17.80
1/2	12.70	38.00	24.00	35.00	34.00	10.00	21.95
3/4	19.00	44.00	25.50	41.20	38.00	13.00	27.30
1	25.40	57.00	30.00	50.80	44.00	13.00	34.05
1 1/4	31.80	64.00	33.50	57.00	45.00	13.00	42.80
1 1/2	38.00	76.00	39.50	67.00	47.00	13.00	48.90
2	51.00	92.00	43.00	83.00	59.00	16.00	61.35
2 1/2	63.50	108.00	46.00		61.00	16.00	74.20
3	76.00	127.00	54.00		63.00	16.00	90.15
4	102.00	159.00	60.50		69.00	19.00	115.80